

cloud

i90

IMU-RTK GNSS  
RECEIVER



SURVEYING &  
ENGINEERING

cloud

# HIGH-PERFORMANCE IMU RTK GNSS RECEIVER

The i90 GNSS receiver integrates professional IMU-RTK technology to provide a robust and accurate positioning, in any circumstances. It combines state-of-the-art GNSS RTK engine, a calibration-free high-end IMU sensor and advanced GNSS tracking capabilities to dramatically increase RTK availability and reliability.

The i90 automatic pole-tilt compensation boosts survey and stakeout speed by up to 30%. Construction and land surveying projects are achieved with high productivity and reliability pushing the boundaries of conventional GNSS RTK survey.

## FULL GNSS POSITIONING

**Combining GPS, Glonass, Galileo and BeiDou constellations.**

The embedded 624-channel GNSS technology takes benefit from all GPS, GLONASS, Galileo and BeiDou signals and provides robust RTK position availability and reliability.

## HASSLE-FREE IMU-RTK SURVEYING

**Dramatically increase RTK availability.**

No complicated calibration process, rotation, leveling or accessories are necessary with the i90. Simply rock the range pole a few times to initialize the i90 internal IMU module and enable GNSS RTK survey in difficult field environment.

## EXTENDED CONNECTIVITY

**Instant NFC pairing of your controller.**

The i90 GNSS combines high-end connectivity modules: Bluetooth, Wi-Fi, NFC, 4G, and UHF radio modem. The 4G modem brings ease of use when working within RTK networks. The internal UHF radio modem allows long-distance base-to-rover surveying up to 5 km.

## EXTENDED CONNECTIVITY

**Boost survey and stakeout speed by up to 30%.**

The i90 GNSS build-in IMU ensures interference-free and automatic pole-tilt compensation in real-time. 3 cm accuracy is achieved with pole-tilt range of up to 30 degrees.

cloud

 **IMU-RTK  
TECHNOLOGY**



**ENABLE GNSS RTK  
ANYTIME, ANYWHERE**

---

# SPECIFICATIONS

GNSS Performance <sup>(1)</sup>	
Channels	624 channels
GPS	L1 C/A, L2C, L2P, L5
GLONASS	L1, L2
Galileo	E1, E5a, E5b
BeiDou	B1, B2, B3
SBAS	L1
QZSS	L1, L2, L5

GNSS Accuracies <sup>(2)</sup>	
Real time kinematics (RTK)	Horizontal: 8 mm+ 1 ppm RMS
	Vertical: 15 mm+ 1 ppm RMS
	Initialization time: < 10 s
	Initialization reliability: >99.9%
Post-processing kinematics (PPK)	Horizontal: 2.5 mm+ 1 ppm RMS
	Vertical: 5 mm+ 1 ppm RMS
Post-processing static	Horizontal: 2.5 mm+ 0.5 ppm RMS
	Vertical: 5 mm+ 0.5 ppm RMS
Code differential	Horizontal: 0.25 m RMS
Autonomous	Horizontal: 1.5 m RMS
	Vertical: 3 m RMS
Positioning rate	Up to 10 Hz
Time to first fix <sup>(3)</sup>	Cold start: < 45 s
	Hot start: < 10 s
	Signal re-acquisition: < 1 s
RTK tilt-compensated	Additional horizontal pole-tilt uncertainty typically less than 10 mm+ 0.7 mm/° tilt

Hardware	
Size (L x W x H)	159 mm x 150 mm x 110 mm (6.3 in x 5.9 in x 4.3 in)
Weight	1.26 kg (2.77 lb)
Environment	Operating: -40°C to +65°C (-40°F to +149°F)
	Storage: -40°C to +85°C (-40°F to +185°F)
	Humidity
Ingress protection	IP67 waterproof and dustproof, protected from temporary immersion to depth of 1 m
Shock	Survive a 2-meter pole drop
Tilt sensor	Calibration-free IMU for pole-tilt compensation. Immune to magnetic disturbances. E-Bubble leveling
Front panel	4 LED indicates 1.46" OLED Display

Certifications	
FCC Part 15 (class B Device), FCC Part 22, 24, 90; CE Mark; NGS Antenna Calibration; MIL-STD 810G, Method 514.7	


Communication		
Network modem	Integrated 4G modem LTE (FDD): B1, B2, B3, B4, B5, B7, B8, B20 DC-HSPA+/HSPA+/HSPA/UMTS: B1, B2, B5, B8 EDGE/GPRS/GSM 850/900/1800/1900 MHz	
	Wi-Fi	802.11 b/g/n, access point mode
Bluetooth ®	v4.1	
Ports	1 x 7-pin LEMO port (external power, RS-232)	
	1 x USB Type-C port (data download, firmware update)	
	1 x UHF antenna port (TNC female)	
UHF radio	Standard Internal Rx/Tx: 410 - 470 MHz Transmit Power: 0.5 W to 2 W Protocol: CHC, Transparent, TT450, 3AS Link rate: 9600 bps to 19200 bps Range: Typical 3 km to 5 km RTCM 2.x, RTCM 3.x, CMR input/output	
	Data formats	HCN, HRC, RINEX 2.11, 3.02 NMEA 0183 output NTRIP Client, NTRIP Caster
	Data storage	32 GB internal memory

Electrical	
Power consumption	5 W (depending on user settings)
Li-ion battery capacity	2 x 3400 mAh, 7.4 V
Operating time on internal battery <sup>(4)</sup>	UHF receive/transmit (0.5 W): 6 h to 9 h
	Cellular receive only: up to 9 h Static: up to 10 h
External power input	9 V DC to 28 V DC



\*All specifications are subject to change without notice.

(1) Compliant, but subject to availability of BDS ICD and Galileo commercial service definition. BDS B3 and Galileo E6 will be provided through future firmware upgrade. (2) Accuracy and reliability are determined under open sky, free of multipaths, optimal GNSS geometry and atmospheric condition. Performances assume minimum of 5 satellites, follow up of recommended general GPS practices. (3) Typical observed values. (4) Battery life is subject to operating temperature.



© 2020 Shanghai Huace Navigation Technology Ltd. All rights reserved. The CHC and CHC logo are trademarks of Shanghai Huace Navigation Technology Limited. All other trademarks are the property of their respective owners. Revision May 2020.