## cloud

# D230

SINGLE BEAM ECHO SOUNDER



(+)

MARINE SURVEY & CONSTRUCTION

### cloud

### COST-EFFECTIVE SINGLE BEAM ECHO SOUNDER

The D230 is a single beam echo sounder making hydrographic surveying simpler and more productive. Particularly design for shallow water bathymetric survey, the D230 features and sounding accuracy of  $\pm$  0.01 m + 0.1% x D and a detection range 0.15 m to 200 m.

Advanced water depth analysis algorithm filters the secondary echo automatically and professional depth-keeping configuration ensures accurate results by eliminating noise interference. The gain, power and range are also adjusted automatically.

### INTEGRATED ECHO-SOUNDER FOR SHALLOW WATER

# Affordable and professional for any bathymetric survey in shallow water.

- · 200 KHz transducer for shallow water surveying
- · Compact and portable with consistent and accurate results
- · Easy to connect with your computer and GNSS receiver
- · Anti-interference technology automatically filters second echo
- · Software controlled with automatic parameter adjustments

### cloud





# PROFESSIONAL SINGLE BEAM ECHOSOUNDER

#### **SPECIFICATIONS**

Measurement Parameters	
Detection Range	0.15 m to 200 m
Resolution	0.01 m
Accuracy	± 0.01 m + 0.1% x D (D = water depth)
Frequency	200 KHz
Sound Velocity Adjustment Range	1300 m/s to 1700 m/s
Beam Angle	6.5° ± 1°
Data Type	CHCNAV, NAME SDDPT/SDDBT, Original waveform

Physical		
Size (L x W x H)	24 cm × 16 cm × 6.5 cm (host) 25.7 cm × 12cm × 6.4 cm (transducer)	
Weight	1.1 kg (host) 2.15 kg (transducer)	
Pulse Power	300 W	
External Power	10 - 30 VDC	
Operating Temperature	-30°C to +60°C (-22°F to +140°F)	



\*All specifications are subject to change without notice.

© 2020 Shanghai Huace Navigation Technology Ltd. All rights reserved. The CHC and CHC logo are trademarks of Shanghai Huace Navigation Technology Limited. All other trademarks are the property of their respective owners. Revision May 2020.